

# LIQUID DUMP VALVES LEVER OPERATED



## CODE BUILDER D SERIES

Series:

**D = Dump Valve**

Model:

**LD = Lever Operated Diaphragm Balanced**  
 LP = Lever Operated Piston Balanced Throttle (2 & 3 inch only)  
 LB = Lever Operated Piston Balanced

Line Size:

**2 = 2 NPS**  
 3 = 3 NPS  
 4 = 4 NPS  
 6 = 6 NPS

End Connection:

**SA = FNPT (2 & 3 NPS only)**  
 AR = 150RF

Body Type:

**A = Angle**  
 T = Thru

Shell Material:

**D = Ductile Iron**

Inner Valve Size:

**F = Full Port**  
 R = Reduced Port (LP only)

Actuator:

**L = Lever Operated**

Service Type:

**S = Standard**  
 C = Corrosive  
 K = Corrosive with Coated Shell Components

**D LD 2 SA A D F L S**

Options: Additional cost and lead times will apply  
 If multiple options required input in sequential order  
 Leave blank if no options required

1 = NACE Certification (Corrosive Option Only)  
 2 = Hydrostatic Test Certification  
 3 = MTR (Shell Components)  
 H = HSN Elastomers  
 V = FKM Elastomers  
 X = Export (Hydrostatic test, MTR & 3.1)

Not all selections available on all products listed.  
 See product pages 03:10.1 - 03:20.7 for available options