

FLOAT OPERATED CONTROLLERS



CODE BUILDER F SERIES (LEVEL CONTROLS)

Series:

F = Float Operated Controllers

Model:

PC = GEN II Pneumatic Level Controller
 EC = Electric Level Controller (Back Mount only)
 PL = GEN 3 Pneumatic Level Controller

Connection Size:

2 = 2 NPS
 3 = 3 NPS
 4 = 4 NPS
 5 = 5 NPS (HU only)
 6 = 6 NPS

End Connection:

S4 = 4000 psi MNPT - 2 inch only

AR = 150 RF
 BR = 300 RF
 DR = 600 RF
 ER = 900 RF
 FR = 1500 RF
 DJ = 600 RTJ
 EJ = 900 RTJ
 FJ = 1500 RTJ
 HU = Hammer Union - 3,4,5 inch only
 GV = Grooved - 2 inch L & R only (PC & EC only)

Mounting Type:

L = Left Side Mount
 R = Right Side Mount
 B = Back Mount (PC & EC only)

Displacer Type:

Displacer Extensions:

A = None
 B = 6 inch
 C = 12 inch
 D = 18 inch

1 = 1 7/8 x 12

2 = 1 7/8 x 20

3 = 2 3/4 x 14 1/4

4 = 2 1/2 x 12

5 = 1 7/8 x 5 11/16

6 = 1 3/4 x 12

7 = 1 3/4 x 20

Poly
4000 psi

316SS
2000 psi

Service Type:

S = Standard LCC body
 C = Corrosive (S6 body)

F PC 2 S4 B 1 A S

Options: Additional cost and lead times will apply
 If multiple options required input in sequential order
 Leave blank if no options required

1 = NACE Certification (Corrosive Option Only)
 2 = Hydrostatic Test Certification
 3 = MTR (Shell Components)
 A = AFLAS Elastomer
 H = HSN Elastomer
 X = Export (Hydrostatic test, MTR & 3.1)

Not all selections available on all products listed.
 See product pages 08:10.1 - 08:30.3 for available options